


SQR Series

Plugs for Square Tubing



SQR Series square plugs feature a series of externally tapered ribs designed to accommodate a wide range of tubing gauges while also satisfying fit adjustments inside dimensional fluctuations. The exterior ribs are designed to provide a sure grip inside a tube without unattractive plastic shavings found on many straight wall glide installations. SQR Series square plugs are not subject to rust or corrosion.



Material: Low-Density Polyethylene **Color:** Black

White Glides - Various SQR parts are available in white. These part numbers are noted on chart in *red italics*.

Plugs for Square Tubing SQR Series

Caplugs No.	Dimensions				Packaging	
	A-To Fit Tube Size O.D.	Gage (Wall Thickness)	B		Carton Quantity	Mini Pak Quantity
			In	mm		
SQR-1/2-16-18	.500	16 - 18 Ga. (.065 - .049)	.44	11.17	5000	1000
SQR-5/8-14-20	.625	14 - 20 Ga. (.083 - .035)	.43	10.92	5000	1000
SQR-3/4-10-14	.750	10 - 14 Ga. (.134 - .083)	.43	10.92	2500	500
<i>SQR-3/4-14-20 WHT</i>	.750	14 - 20 Ga. (.083 - .035)	.43	10.92	2500	500
SQR-7/8-14-20	.875	14 - 20 Ga. (.083 - .035)	.43	10.92	3000	600
<i>SQR-1-10-14 WHT</i>	1.000	10 - 14 Ga. (.134 - .083)	.43	10.92	2500	500
SQR-1-10-14 THICK HEAD	1.000	10 - 14 Ga. (.134 - .083)	.43	10.92	2000	400
<i>SQR-1-14-20 WHT</i>	1.000	14 - 20 Ga. (.083 - .035)	.43	10.92	2500	500
SQR-1-14-20 THICK HEAD	1.000	14 - 20 Ga. (.083 - .035)	.43	10.92	1000	200
SQR-1-1/8-14-20	1.125	14 - 20 Ga. (.083 - .035)	.49	12.45	1500	300
SQR-1 1/4-10-14	1.250	10 - 14 Ga. (.134 - .083)	.52	13.21	1000	200
<i>SQR-1-1/4-14-20 WHT</i>	1.250	14 - 20 Ga. (.083 - .035)	.52	13.21	1000	200
SQR-1 3/8-10-14	1.375	10 - 14 Ga. (.134 - .083)	.52	13.21	1000	200
SQR-1 3/8-14-20	1.375	14 - 20 Ga. (.083 - .035)	.52	13.21	1000	200
<i>SQR-1-1/2-10-14 WHT</i>	1.500	10 - 14 Ga. (.134 - .083)	.52	13.21	1000	200
<i>SQR-1-1/2-14-20 WHT</i>	1.500	14 - 20 Ga. (.083 - .035)	.52	13.21	1000	200
SQR-1 3/4-10-14	1.750	10 - 14 Ga. (.134 - .083)	.52	13.21	500	100
SQR-1-3/4-14-20	1.750	14 - 20 Ga. (.083 - .035)	.52	13.21	500	100
SQR-2-4-8	2.000	4 - 8 Ga. (.238 - .165)	.52	13.21	500	100
<i>SQR-2-10-14 WHT</i>	2.000	10 - 14 Ga. (.134 - .083)	.52	13.21	500	100
SQR-2-14-20	2.000	14 - 20 Ga. (.083 - .035)	.52	13.21	500	100
SQR-2-1/4-10-14	2.250	10 - 14 Ga. (.134 - .083)	.52	13.21	200	40
SQR-2-1/2-6-10	2.500	6 - 10 Ga. (.203 - .134)	.56	14.22	300	60
SQR-2 1/2-16-23	2.500	16 - 23 Ga. (.065 - .025)	.56	14.20	300	60
SQR-SQ-20-1	2.500	10 - 14 Ga. (.134 - .083)	.50	12.70	500	100
SQR-SQ-22-3	2.750	14 - 20 Ga. (.083 - .035)	.65	16.51	200	40
SQR-SQ-22-4	2.750	8 - 14 Ga. (.165 - .083)	.73	18.54	200	40
SQR-SQ-24-1	3.000	3 - 7 Ga. (.259 - .180)	.50	12.70	400	80
SQR-SQ-25-3	3.125	6 - 11 Ga. (.203 - .120)	.97	24.64	150	65
SQR-80mm	80 mm	2.5 - 5.6 mm	.98	24.89	100	20
SQR-SQ-30-3	3.500	6 Ga. (.203)	.69	17.53	100	20
SQR-SQ-30-4	3.500	14 - 20 Ga. (.083 - .035)	.69	17.53	100	20
SQR-SQ-31-3	3.875	4 - 8 Ga. (.238 - .165)	1.00	25.40	200	40
SQR-SQ-32-3	4.000	4 - 11 Ga. (.238 - .120)	.91	23.11	150	30
SQR-100mm	100 mm	5-6.3 mm	.98	24.89	75	15
SQR-SQ-38	4.750	6 - 11 Ga. (.203 - .120)	1.00	25.40	100	20
SQR-5-3-10	5.000	3 - 10 Ga. (.259 - .134)	.98	24.90	75	15
SQR-6-3-10	6.000	3 - 10 Ga. (.259 - .134)	.98	24.90	50	10