

“Stay Connected” with



Liquid Tight Cordgrips

a PennEngineering® Company



Heyco®-Tite Brass Liquid Tight Cordgrips

NPT Hubs


The Ultimate in Liquid Tight Strain Relief Protection

**HIGH
TEMPERATURE**

- Nickel plated brass construction for superior protection of flexible cables.
- Nickel-plated finish over brass provides excellent corrosion resistance and durability.
- IP 68/ IP 69K rated.
- For use in threaded holes.
- Multiple sizes for flexible cord diameters ranging from .118" (3,0 mm) to 2.047" (52,0 mm).
- We recommend using the smallest cordgrip that accommodates your cable size.
- Sealing gland is molded in Fluorine Rubber (FPM) Material which provides great heat resistance.
- DFARS Compliant
- Strain relief: Version A acc. to EN 62444

| CABLE DIA. RANGE | | | | PART NO. | THREAD SIZE * | PART DIMENSIONS | | | | | |
|------------------|------|---------|------|--------------|---------------|--------------------------|------|-----------------------|------|-----------------------------|------|
| Minimum | | Maximum | | | | A Max. O.A. Length | | B Thread Length | | C Wrenching Flat Size | |
| in. | mm. | in. | mm. | | | in. | mm. | in. | mm. | in. | mm. |
| .118 | 3,0 | .157 | 4,0 | 14890 | NPT 1/8 | .905 | 23,0 | .315 | 8,0 | .512 | 13,0 |
| .157 | 4,0 | .236 | 6,0 | 14891 | | | | | | | |
| .138 | 3,5 | .197 | 5,0 | 14892 | NPT 1/4 | 1.142 | 29,0 | .472 | 12,0 | .591 | 15,0 |
| .197 | 5,0 | .256 | 6,5 | 14893 | | | | | | | |
| .256 | 6,5 | .315 | 8,0 | 14894 | | | | | | | |
| .236 | 6,0 | .413 | 10,5 | 14895 | | | | | | | |
| .315 | 8,0 | .591 | 15,0 | 14896 | NPT 1/2 | 1.417 | 36,0 | .590 | 15,0 | .945 | 24,0 |
| .492 | 12,5 | .807 | 20,5 | 14897 | NPT 3/4 | 1.575 | 40,0 | .590 | 15,0 | 1.181 | 30,0 |
| .669 | 17,0 | 1.004 | 25,5 | 14898 | NPT 1 | 1.890 | 48,0 | .787 | 20,0 | 1.417 | 36,0 |
| .945 | 24,0 | 1.122 | 28,5 | 14899 | NPT 1-1/4 | 2.008 | 51,0 | .787 | 20,0 | 1.811 | 46,0 |
| 1.299 | 33,0 | 1.614 | 41,0 | 14900 | NPT 1-1/2 | 2.205 | 56,0 | .866 | 22,0 | 2.165 | 55,0 |
| 1.575 | 40,0 | 2.047 | 52,0 | 14901 | NPT 2 | 2.323 | 59,0 | .866 | 22,0 | 2.756 | 70,0 |

*Tapped hole required to maintain ratings. Standard NPT K/O hole can be used only if sealing is not required.



*Quick
Specs*

Material: Nickel plated brass w/ FPM (viton) gland
 Temp Rating: -40°F (-40°C) to 392°F (200°C)
 IP rating: IP68/ IP 69K